

CP 333



Available colours

UNI+ polyester putty

CP 333 Universal Polyester Putty stands as a high-strength filler designed for versatile surface shaping. This putty provides excellent adhesion to various substrates and is characterized by its ease of application and processing.

However, it's important to note that **CP 333** cannot be used on surfaces in direct contact with foodstuffs and drinking water. Conveniently available in a 2 kg package, **CP 333** offers a practical solution for a range of surface shaping applications, ensuring strength and reliability in use.

PACKAGING	
Volume	Collective packaging
2 kg + 40 g hard.	4 pcs. + 4 pcs.



EASY TO PROCESS



ADHESION



HIGH DURABILITY



POT LIFE
5-6 min after mixing with hardener



MINIMUM SHELF LIFE
12 months in originally sealed packaging



VOC
2004/42/WE IIB(b) (250) 45

PROCESS

PROCESS

PROCESS



SUBSTRATE PREPARATION
The product is applied to a previously sanded and cleaned substrate. Old coatings should be removed. The most effective method is application on an epoxy primer **CP 394**. Do not apply putty on top of reactive primer



MIXING RATIO
100 parts of CP 333
Hardener:
< 10°C - 3-3.5%
10-20°C - 2-2.5%
> 20°C - 11.5%



APPLICATION
Application in several thin coats. After each of these, the product should be cured



MIXING BEFORE USE
The product must be mixed before and after adding the hardener



DRYING
Drying times at 20°C and 65% relative humidity:
- 20-30 min



IR DRYING
~5 min, do not exceed 80°C



GRINDING
Coarse (dry): **P100-P120**
Finishing (dry): **P120-P240**